

## UV Curing Units

### HIGHLIGHTS

Best casting results

Low power consumption

Simple use and maintenance

Timer setting



### UV Curing Unit 'S' and 'M'

The UV Curing Unit device concurs the secondary solidification of the models built by the DigitalWax® systems. These models are perfectly formed, but they need an additional exposure to a specific UV light source. This allows the consolidation and the stabilization of their structure and ensures the best casting results.

UV Curing Unit model "S2" is usually suggested for DigitalWax® 008J and DigitalWax® 028J, while the model "M" is more suitable for DigitalWax® 029J because it can cure a complete platform all at once.

Technical data:	UV Curing Unit 'S2'	UV Curing Unit 'M'
Ventilation	Forced ventilation inside	Forced ventilation inside
User controls	On/Off button Timer Safety device on door opening	On/Off button Timer Safety device on door opening
Timer setting	0 ÷ 30 minutes	0 ÷ 30 minutes
Curing area dimensions	160 x 160 x 160 mm	225 x 250 x 225 mm
Machine size	265 x 300 x 330 mm	370 x 330 x 480 mm
Weight	11.8 kg	20.5 kg
Power consumption	35 W	120 W
Power supply	90-264 V / 50-60 Hz	220 V / 50-60 Hz

Technical specifications subject to changes without notice.