

DWS develops high-tech solutions for jewellery and the fashion sector.

High resolution, definition, accuracy, details' precision. DWS 3D printers have no rivals in the sector, thanks to the continuous research conducted by R&D department, who not only designs the 3D printers, but also the materials (castable and functional) and the proprietary software: a fully integrated system that guarantees the complete control over all processes and the necessary components for the realization of the objects.

Among the new applications and technologies, innovative concepts stand out: the 3D printing cluster for direct investment casting (XCLUSTER), the printing of already linked chains (XCLUSTER Chain) and the printing of finished products featuring transparent textures and surfaces, reproducing natural ceramic or suitable for customization with traditional treatments.

Thanks to the combination of materials, stereolithographic 3D printer and a specially designed software, the workflow becomes fully digital and automated. This increases companies' productivity, reducing time to market and decreasing production times and costs.

APPLICATIONS

THE JEWEL

The detail	6
The chain jersey	8
he pave	10
The filigrees	12
The cluster	14
The ceramic	16
The master models	18
The chain	20

FASHION AND DESIGN

The particular	22
The colors	24
The molds	26
The functional materials	28

3D PRINTERS AND MATERIALS

THE JEWEL

The detail	32
The chain jersey	33
The pave	34
The filigrees	35
The cluster	36
The ceramic	37

The master models	38
The chain	39
FASHION AND DESIGN	
The particular	40
The colors	41
The molds	42
The functional materials	43
SOFTWARE	
SOFTWARE	44

TECHNICAL DATA SHEETS

TECHNICAL DATA SHEETS 46

UV CURING UNITS

UV CURING UNIT	> >	50	0
----------------	--------	----	---

TΗ	E	J	E١	W	EI	

The detail

6

7

THE JEWEL

The detail

Accurate details, high definition, ideal angles, minimum thicknesses for your most detailed creations, for your desires of perfection. Laser precision, together with the resins' quality, allows the highest possible precision in printing and in casting. Undercuts, cavities, complex geometries are no longer an issue and the supports' easy removal completes an approach that helps the user in expressing his creativity.

IDEAL OUTLINES

UNDERCUTS

COMPLEX GEOMETRIES

FASY TO REMOVE SUPPORTS

DIMENSIONAL RESPECT

SMOOTH SURFACES

PRECISE CASTING

THIN THICKNESSES





The chain jersey

It is no longer a mirage obtaining already linked objects without the need of welding.

The realization of bracelets, necklaces, accessories resembling a jersey that, once cast, presents the precision and the flexibility of a knitted tissue. An amazing result, free from link-by-link welding.

SMOOTH SURFACES

UNDERCUTS

PRECISE CASTING

COMPLEX GEOMETRIES

INTERTWINED TISSUE EFFECT

EASY TO REMOVE SUPPORTS

PRECISE AND INDEPENDENT LINKS

DIMENSIONAL RESPECT



THE JEWEL

The pave

The extreme dimensional precision, together with materials' quality, allows the stones' pre-set before investment casting.

Smooth surfaces and no need for manual finishing ensure a result optimizing production procedures. Stones' setting is easy, even with complex housings, and the casting precise, also thanks to the memory form effect of DWS materials.

CAVITIES SMOOTH SURFACES **PRECISE CASTING** FASY TO REMOVE SUPPORTS UNDERCUTS **EASY STONES AND MICROPAVE SETTING IDEAL OUTLINES** DIMENSIONAL RESPECT

THE JEWEL

The filigrees



The filigrees

The thinnest thicknesses at the highest definition. Filigrees' direct casting has never been so precise. Complex geometries, intertwined threads, precise casting.



The cluster



The cluster

Productivity at the service of precision. A unique system. DWS cluster system allows to preserve the highest definition and dimensional respect, increasing the productivity by making the most of Z axis stroke. The system uses sprues as supports, being it able to vary their dimensions and diameters to optimize production. Thanks to NAUTA XCLUSTER software, the maximum definition joins a high productivity.

SMOOTH SURFACES

CAVITIES

HIGH PRODUCTIVITY

EASY TO REMOVE SUPPORTS

PRECISE CASTING

UNDERCUTS

DIMENSIONAL RESPECT



THE JEWEL

The ceramic





A nanoceramic material to create objects recalling the same properties of artisan ceramics: a blank canvas where unleashing your chromatic creativity. The material resists at 180° C, and, after the coating in enamel, in various customized colors, must be placed in an oven to obtain a result identical to porcelain.



Т	Н	Е	J	E)	W	Έ	L

The master models

The best resolution for master models dedicated to vulcanized rubber molding (RTV or HTV). Detailed and thin models at the service of jewellery. DWS resins for master models are also ideal for molds to be vulcanized to produce objects in zamac.





The chain

With the cluster system (NAUTA XCLUSTER Chain software), DWS allows the printing of chains with different dimensions and design with castable material. They can be reproduced complete of clasps and terminals, already linked, with no need for welding and internally empty. Supports working as sprues, high definition, high productivity, and low costs.



INDEPENDENT AND PRECISE CHAIN LINKS

PRECISE OUTLINES

COMPLEX GEOMETRIES

SMOOTH SURFACES

EASY TO REMOVE SUPPORTS

PRECISE CASTING

DIMENSIONAL RESPECT





Shoulder bag, buckles, clasps, stoppers, cord locks, logos, finishings... All details of the fashion world can be realized both in functional and castable resins. These are ideal solutions to produce cast metal details and those in elastic materials, in textured resins and in resistant materials to be customized in color.

High productivity and maximum flexibility for pre-productions and productions dedicated to the most valuable creations.



FASHION AND DESIGN

The colors

Printing digital stones, transparent or translucent, and potentially in any color, is everyday normality for DWS. Faceted or smooth stones, with no geometrical limits, ideal for the creation of accessories and applications in all the fields of fashion.

DIMENSIONAL RESPECT

UNDERCUTS

TRANSPARENCIES

PRECISE OUTLINES

COMPLEX GEOMETRIES

EASY TO REMOVE SUPPORTS

COLORS AND SHADES

SMOOTH SURFACES



The molds



The molds

Free to print molds and always be in time to market, even on remarkable dimensions. Materials are suitable for resisting high temperatures, accurate printing processes able to replace traditional molds, the highest quality surfaces.





The functional materials



Printing highly rigid materials, flexible materials, resistant to high temperatures and ready to join fashion creations ones.

The available range of functional resins, together with the precision and high productivity of the printers, allows the realization of final and ready to use details or suitable to the finish.

SMOOTH SURFACES

CAVITIES

REBOUND EFFECT

PRECISE OUTLINES

COMPLEX GEOMETRIES

RESISTANT MATERIALS

PRODUCTIVITY

UNDERCUTS

HIGH TEMPERATURES MATERIALS

DIMENSIONAL RESPECT





3D PRINTERS AND MATERIALS

The detail



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia 444	Casting			_	_			-
Fusia 445	Casting							
Fusia DC300	Casting	_	A			_	_	
Fusia DC400	Casting	-				_	-	
Fusia DC500	Casting	_				_	_	
Fusia DC550	Casting	_				_	_	
Fusia DC800	Casting					_	_	
Fusia DC900	Casting							

The chain jersey



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia DC300	Casting	_				_	-	
Fusia DC400	Casting	-				_	_	
Fusia DC500	Casting	-				_	-	
Fusia DC900	Casting							

THE JEWEL

The pave



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia 444	Casting			-	-			_
Fusia 445	Casting							
Fusia DC300	Casting	_				_	_	
Fusia DC400	Casting	_				_	_	
Fusia DC500	Casting	_				_	_	
Fusia DC550	Casting	_				_	_	
Fusia DC800	Casting					-	_	
Fusia DC900	Casting							

The filigrees



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia 444	Casting			_	-			_
Fusia 445	Casting							
Fusia DC300	Casting	_				_	_	
Fusia DC700	Casting	_				_	_	
Fusia DC710	Casting	_				_	_	
Fusia DC800	Casting	_				_	_	
Fusia DC900	Casting							
Fusia DC905	Casting							



The cluster



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia 445	Casting							
Fusia DC905	Casting							

The ceramic



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Irix A	Ceramic-like	_					_	

The master models



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Precisa 780	Moulding		_	_	-	_	_	_
Precisa DL260	Moulding	-						
Therma 289	Moulding		_	-	-	_	-	_
Therma 294	Moulding		_	_	-	_	_	_
Therma DM210	Moulding	_						
Therma DM220	Moulding	-						
THE JEWEL

The chain



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Fusia 445	Casting							
Fusia DC900	Casting							
Fusia DC905	Casting							



The particular



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Invicta 915	Functional material	_	_	-				
Invicta 917	Functional material	_	_	_				
Invicta DL370	Functional material	_	_	_				
Invicta DL380	Functional material	_	_	_				
Invicta DL385	Functional material	_	_	_				
Invicta DL390	Functional material	_	_	_				
Invicta DL395	Functional material	_	_	-				
Invicta DL405	Direct manufacturing	_	_	_				
Invicta DL406	Direct manufacturing	_	_	_				
Invicta 2020	End-use products	_	_	_				
Invicta AB001	ABS-like	_	_	-				
Invicta AB002	ABS-like	_	_	_				

FASHION AND DESIGN

The colors



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Irix	Digital Stone	_						
Irix V	Digital Stone							

The molds



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Therma DM500	Molds production	_	_	_				

The functionals materials



Materials	Feature	XFAB 2500HD	XFAB 3500HD	028J Plus	029JL2/X/XC	XPRO S	XPRO SL	XPRO Q
Invicta 915	Functional material	-	_	_				
Invicta 917	Functional material	-	_	_				
Invicta DL370	Functional material	-	_	_				
Invicta DL380	Functional material	_	_	_				
Invicta DL385	Functional material	_	_	_				
Invicta DL390	Functional material	_	_	_				
Invicta DL395	Functional material	_	_	_				
Invicta DL405	Direct manufacturing	_	_	_				
Invicta DL406	Direct manufacturing	_	_	_				
Invicta 2020	End-use products	-	_	_				
Invicta AB001	ABS-like	_	_	_				
Invicta AB002	ABS-like	_	_	_				
Flexa GM08	Rubber-like	_	_	_				
Flexa GM08B	Rubber-like	_	_	_				
Flexa GM010	Rubber-like	_	_	-				
Vitra DL375	Transparent	_	_	_				_





NAUTA® SOFTWARE SUPPORTS THE MODEL, NO MATTER THE SHAPE

NAUTA® software creates super light supports and replicates.

Developed in-house, this DWS parametric software prepares the file to be 3D printed, allowing to put in place the whole set of supports and the positioning of the models on the virtual platform before the file is sent to FICTOR, the printer management software.

NAUTA+ offers automatic functions optimizing: the supports' number, the orientation of the object to be printed and the platform filling made easier thanks to istancing. The supports created by NAUTA+ have a patented break point in order to remove them easily without the use of specific tools. Moreover, the innovative lattice function, also patented by DWS, allows the creation of an extremely light set of supports.

The software also estimates the object's weight and the expected resin consumption.

NAUTA® XCLUSTER® and **NAUTA® XCLUSTER® CHAIN** represent additional modules, and they allow, respectively, to develop the printing phase along the whole Z axis stroke and to build already linked chains made by independent elements, exploiting the cluster concept patented by DWS.

Both the modules have been developed in order to obtain the maximum productivity by exploiting both vertical construction and cluster concept, that allows to apply the least possible number of supports, which provides a completely usable structure during the casting phase, as sprues are used as supports.





	XFAB 2500HD	XFAB 3500HD
Technology	Laser Stereolithography	Laser Stereolithography
Working Area	Ø 180 x 180 mm	140 x 140 x 180 mm
Laser Source	Solid State BlueEdge®	Solid State BlueEdge®
Layer Thickness	10-100 micron (mechanical resolution, the actual value depends on the material used)	10-100 micron (mechanical resolution, the actual value depends on the material used)
Scanning Method	Galvanometer	Galvanometer
Software	XFAB® Edition FICTOR® and NAUTA®+ included	XFAB® Edition FICTOR® and NAUTA®+ included
Input Files Format	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x
Machine Size	400 x 606 x 642 mm	400 x 606 x 762 mm
Weight	31 Kg	40 Kg
Operating Temperature and Humidity	20°-25°C / 60%	20°-25°C/60%
Power Supply	24V DC con AC 240/100V / 50-60 Hz External Supplier Included	24V DC con AC 240/100V / 50-60 Hz External Supplier Included
Electrical Consumption	160W	160W
PC Minimum Requirements	Windows 8 or Above*	Windows 8 or above*1
Memory	RAM 4GB*	RAM 4GB*1
Graphic Card	OpenGL 2.0 Compatible or Above*	OpenGL 2.0 Compatible or Above*1
I/O Interfaces	1 USB port	1 USB Port - 1 Ethernet TCP/IP Port
Connectivity	1 Active Internet Connection	1 Active Internet Connection

*The recommended requirements may vary in accordance with the complexity of the file to be printed.

¹Built-in PC, the minimum requirements are expressed in order to operate NAUTA*+ with an external PC (not included). Technical specifications subject to change without notice.

TECHNICAL DATA SHEET



028J Plus Series

Laser Stereolithography
90 x 90 x 90 mm
Solid State BlueEdge®
10-100 micron (mechanical resolution, the actual value depends on the material used)
Galvanometer
FICTOR® and NAUTA®+ included
.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x
380 x 515 x 733 mm
56 Kg
20°-25°C/60%
AC 230V / 50 Hz
400 W
External PC included
-
-
1 USB port - 1 TCP/IP ethernet port

Technical specifications subject to change without notice..







	029JL2	029X	029XC
Technology	Laser - Stereolithography	Laser - Stereolithography	Laser - Stereolithography
Working Area	110 x 110 x 200 mm	150 x 150 x 200 mm	170 x 170 x 200 mm
Laser Source	Solid State BlueEdge®	Solid State BlueEdge®	Solid State BlueEdge®
Layer Thickness	10-100 micron (mechanical resolution, the actual value depends on the material used)	10-100 micron (mechanical resolution, the actual value depends on the material used)	10-100 micron (mechanical resolution, the actual value depends on the material used)
Scanning Method	Galvanometer	Galvanometer	Galvanometer
Software	FICTOR® and NAUTA®+ included	FICTOR® and NAUTA®+ included	FICTOR® and NAUTA®+ included
Input Files Format	stl, .slc, .nauta, .fi ctor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x	stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x
Machine Size	610 x 660 x 1400 mm	610 x 660 x 1400 mm	610 x 660 x 1400 mm
Weight	150 Kg	150 Kg	150 Kg
Operating Temperature and Humidity	20°-25°C/60%	20°-25°C/60%	20°-25°C/60%
Power Supply	AC 230V / 50 Hz	AC 230V / 50 Hz	AC 230V / 50 Hz
Electrical Consumption	500W	500W	500W
PC Minimum Requirements	External PC included	External PC included	External PC included
Memory	-	-	-
Graphic Card	-	-	-
I/O Interfaces	1 USB port - 1 TCP/IP ethernet port	1 USB port - 1 TCP/IP ethernet port	1 USB port - 1 TCP/IP ethernet port
Connectivity	1 Active Internet Connection	1 Active Internet Connection	1 Active Internet Connection

Technical specifications subject to change without notice.

TECHNICAL DATA SHEET







	XPRO S	XPRO SL	XPRO Q
Technology	Laser - Stereolithography	Laser - Stereolithography	QUAD Laser - Stereolithography
Working Area	300 x 300 x 300 mm	300 x 300 x 500 mm	300 x 300 x 300 mm
Laser Source	Solid State BlueEdge®	Solid State BlueEdge®	Solid State BlueEdge®
Layer Thickness	10-100 micron (mechanical resolution, the actual value depends on the material used)	10-100 micron (mechanical resolution, the actual value depends on the material used)	10-100 micron (mechanical resolution, the actual value depends on the material used)
Scanning Method	Galvanometer	Galvanometer	Quad-Galvanometer
Software	FICTOR® and NAUTA®+ included	FICTOR® and NAUTA®+ included	FICTOR® and NAUTA®+ included
Input Files Format	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x	.stl, .slc, .nauta, .fictor, .mkr, .3dm, .3ds, .ply, .obj, .lwo, .x
Machine Size	704 x 1446 x 2048 mm	704 x 1446 x 2420 mm	704 x 1446 x 2048 mm
Weight	500 Kg	550 Kg	500 Kg
Operating Temperature and Humidity	20°-25°C/60%	20°-25°C/60%	20°-25°C/60%
Power Supply	AC 230V / 50 Hz	AC 230V / 50 Hz	AC 230V / 50 Hz
Electrical Consumption	500W	500W	500W
PC Minimum Requirements	Windows 8 or Above*1	Windows 8 or Above*1	Windows 8 or Above*1
Memory	RAM 4GB*1	RAM 4GB*1	RAM 4GB*1
Graphic Card	OpenGL 2.0 Compatible or Above*1	OpenGL 2.0 Compatible or Above*1	OpenGL 2.0 Compatible or Above*1
I/O Interfaces	1 USB Port - 1 Ethernet TCP/IP Port	1 USB Port - 1 Ethernet TCP/IP Port	1 USB Port - 1 Ethernet TCP/IP Port
Connectivity	1 Active Internet Connection	1 Active Internet Connection	1 Active Internet Connection

* The recommended requirements may vary in accordance with the complexity of the file to be printed. ¹Built-in PC, the minimum requirements are expressed in order to operate NAUTA*+ with an external PC (not included). Technical specifications subject to change without notice.



FEATURES

	UV Curing Unit "S2"	UV Curing Unit "M"	UV Curing Unit "L"
Ventilation	Forced ventilation inside	Forced ventilation inside	Forced ventilation inside
User controls	On/Off button Timer Safety device on door opening	On/Off button Timer Safety device on door opening	On/Off button Timer Safety device on door opening
Timer setting	0 ÷ 30 minutes	0 ÷ 30 minutes	0 ÷ 30 minutes
Curing volume	160 x 160 x 160 mm	225 x 250 x 225 mm	300 x 300 x 300 mm
Machine size	265 x 300 x 330 mm	370 x 330 x 480 mm	570 x 520 x 518 mm
Weight	11,8 Kg	20,5 Kg	26 Kg
Power consumption	35 W	120 W	70 W
Power supply	90-264 V / 50-60 Hz	220 V / 5060 Hz	90-264 V / 50-60 HZ

Technical specifications subject to changes without notice.

UV Curing Units

UV polymerization devices complete the secondary solidification of the models built with DWS 3D printers.

Even if perfectly formed, models need a further exposition to a UV light source so to complete the polymerization and the stabilization of their structure.

"S2" model is suitable for the polymerization of single models, while "M" model can host a complete platform belonging to the 029 or XFAB range of printers.
"L" model is specifically produced for hosting the XPRO Q and XPRO S large platforms.

- High uniformity of exposure
- Easy to use and in maintenance
- Timer settings



lextures

Colors

Clusters



12 rue Jean Bart 78960 Voisins le Bretonneux

Tel: + 33 (0) 1 30 60 03 33 Email: info@3dsolutions.fr



DWS

Via della Meccanica, 21 36016 Thiene (VI) - Italy T +39 0445 810810 info@dwssystems.com

www.dwssystems.com

MADE IN ITALY