The complete 3D scanning solution for your reverse engineering and design projects



learn more peel-3d.com

TECHNICAL SPECIFICATIONS





	peel 2 CAD-S	peel 2 CAD
Part size range (recommended)	0.05 - 0.5 m (2 – 20 in)	0.3 – 3.0 m (1 – 10 ft)
Accuracy	Up to 0.100 mm (0.004 in)	
Mesh resolution	0.100 mm (0.004 in)	0.250 mm (0.010 in)
Measurement rate	550,000 measurements/s	
Volumetric accuracy (based on part size)	0.300 mm/m (0.0036 in/ft) ¹	
Scanning area	143 x 108 mm (5.6 in x 4.3 in)	380 x 380 mm (15.0 x 15.0 in)
Stand-off distance	380 mm (15 in)	400 mm (15.75 in)
Depth of field	100 mm (4 in)	250 mm (10.0 in)
Light source	White light (LED)	
Texture resolution	50 to 250 DPI	50 to 150 DPI
Positioning methods	Geometry and/or targets and/or texture	
Dimensions	154 x 178 x 235 mm (6 x 7 x 9.2 in)	150 x 171 x 251 mm (5.9 x 6.7 x 9.9 in)
Connection standard	1 x USB 2.0	
Output formats	.dae, .fbx, .ma, .obj, .ply, .stl, .txt, .wrl, .x3d, .x3dz, .zpr, .iges, .step, .dxf	
Operating temperature range	5-40°C (41-104°F)	
Operating humidity range (non-condensing)	10–90%	
Certifications	EC Compliance (Electromagnetic Compatibility Directive, Low Voltage Directive), IP50, WEEE	

(1) With positioning targets or with an object presenting adequate geometry for positioning.

peel 2 CAD list of tools and functions



Tools to get the work done



peel 3d, peel 2 CAD, peel 2 CAD-S, and their respective logo are trademarks of Creaform Inc. © Creaform inc. 2021. All rights reserved. V3