

FLX 300

Entry-Level Industrial Desktop

LCD Technology

4K Resolution



Highlights

UV LED array	Extreme uniformity of lighting and high efficiency of printing
4K LCD	Long lifetime of 5000hrs and easy one-piece replacement
40PPI cotton filter	Dust-free protection for light source room
Compact structure	Integrated with 10.1" touch screen and industrial PC
Dual slider	Elevator positioning accuracy of $\pm 3\mu\text{m}$ reaching P-class
Replaceable film	Working cost lowered by replaceable film for resin vat
Environment heater	Temperature in build room controlled by heating system
Printing speed	Normal/super printing mode with speed range of 24-40mm/hr

Technical Data

Build envelope	mm	290 x 165 x 240	Data pre-processing		Polydevs Pro
	in	11.4 x 6.5 x 9.5	Printer controlling		DSCON
Printing speed	mm/hr	15-20 (0.05 mm/layer) / 25-30 (0.1 mm/layer)	Operating system		Windows 10
Accuracy	mm	± 0.1 (150mm standard part)	Touch screen size	in	10.1
		± 0.1 (2mm thickness)	Data transfer interface		USB / Ethernet
Elevator positioning accuracy	μm	$\leq \pm 3$	Power supply		220 VAC, 50 Hz
Elevator rail		Dual slider	Rated power	W	800
Layer thickness	mm	0.05/0.1 (variable)	System control		Closed-loop
Resolution		3840 x 2160	Temperature range	$^{\circ}\text{C}/^{\circ}\text{F}$	22-26 / 72-79
Light source		UV LED array	Max temperature change rate	$^{\circ}\text{C}/\text{hr}$	1
Power density	mw/cm^2	2.5	Relative humidity	%	<40
Pixel size	$\mu\text{m}/\text{pix}$	76	Printer size unpacked	mm	600 x 510 x 900
Wavelength	nm	405	Printer weight unpacked	kg	85
Customer input file format		.stl / .obj / .off / .ply / .3mf	CE certificate		Yes

UnionTech

Shanghai Union Technology Corporation

Room 102, Unit 40, 258 Xinzhuang Rd, Shanghai, 201612, China

enquiry@uniontech3d.cn Tel: +86-021-64978786

www.uniontech3d.com

UnionTech GmbH

Regus Berliner Carree, Berliner Allee 47, 64295 Darmstadt, Germany

info@uniontech3d.de Tel: +49 (0) 6151-2776067

www.uniontech3d.de